

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- · 1.1 Product identifier
- · Trade name: UHU POR FB 50ML*10 L345
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesive
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

E-mail: sds@boltonadhesives.com

Tel.:0049-(0)7223-284-0 Fax: 0049-(0)7223-284-245

- · Further information obtainable from: PSRA
- · 1.4 Emergency telephone number:

Emergency medical information: 8am-10pm (seven days) contact

National Poisons Information Centre, Beaumont Hospital, Dublin 9. Tel 01 8092566

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

STOT SE 3

H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Danger

(Contd. on page 2)

1/11 www.uhu.com



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 1)

· Hazard-determining components of labelling:

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P302+P352 IF ON SKIN: Wash with plenty of water.

P501 Dispose of contents/container in accordance with national regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Adhesive

· Dangerous components:		
EC number: 927-510-4 Reg.nr.: 01-2119475515-33- XXXX	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	50-100%
CAS: 110-82-7 EINECS: 203-806-2 Index number: 601-017-00-1 Reg.nr.: 01-2119463273-41- XXXX	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	≥1-<2.5%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: No special measures required.
- · After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

J)

www.uhu.com 2/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Send for recovery or disposal in suitable receptacles.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Storage class: 3

(Contd. on page 4)

ΙE

www.uhu.com 3/11



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 3)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring	g at the workplace:
---	---------------------

110-82-7 cyclohexane

OEL (Ireland) Long-term value: 700 mg/m³, 200 ppm

IOELV

IOELV (EU) Long-term value: 700 mg/m³, 200 ppm

·DNELs

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics

Oral	Consumer, oral, longterm exposition	149 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	300 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	149 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, longterm exposition	2085 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	477 mg/m³ (rat)

110-82-7 cyclohexane		
Oral	Consumer, oral, longterm exposition	59.4 mg/kg bw/day (rat)
Dermal	Worker, dermal, longterm exposition	2016 mg/kg bw/day (rat)
	Consumer, dermal, longterm exposition	1186 mg/kg bw/day (rat)
Inhalative	Worker, inhalative, shortterm exposition	700 mg/m³ (rat)
	Worker, inhalative, longterm exposition	700 mg/m³ (rat)
	Consumer DNEL, acute inhalation	412 mg/m³ (rat)
	Consumer, inhalative, longterm exposition	206 mg/m³ (rat)

· PNECs

110-82-7 cyclohexane

Fresh water 0.207 mg/l (rat)

Fresh water sediment 3.627 mg/kg dry weight (rat)

Marine water 0.207 mg/l (rat)

Marine sediment 3.627 mg/kg dry weight (rat)

Soil 2.99 mg/kg (rat)
Sewage treatment plant 3.24 mg/l (rat)
Sporadic release 0.207 mg/l

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

(Contd. on page 5)

- IE

www.uhu.com 4/11



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 4)

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- Respiratory protection: Not required.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Recommended thickness of the material: > 0,12 mm

Nitrile rubber. NBR

· Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 10 minutes (Permeation according to EN 374 Part 3: Level 1).

Eye/face protection



Tightly sealed goggles

Goggles recommended during refilling

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Fluid
Yellowish
Characteristic
Not determined.
Undetermined.

· Boiling point or initial boiling point and

boiling range 83-105 °C

· **Flammability** Highly flammable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

· Flash point: -4 °C

• **Decomposition temperature:**• pH

Not determined.

Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 8000 mPas

(Contd. on page 6)

ίΕ·

www.uhu.com 5/11



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version number 16 (replaces version 15) Printing date 22.03.2025 Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

	(Contd. of page
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log	
value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.805 g/cm³
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	All relevant physical data were determined for the
	mixture. All non-determined data are n
	measurable or not relevant for th
	characterization of the mixture.
Appearance:	
Form:	Fluid
Important information on protection of hea	alth
and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	69.2 %
VOC (EC)	69.19 %
Solids content:	30.8 %
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical haz	ard
classes	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit	
flammable gases in contact with water	Void
Oxidising liquids	Void
	Void
Oxidising solids	
Organic peroxides	Void
Oxidising solids Organic peroxides Corrosive to metals Desensitised explosives	Void Void Void

(Contd. on page 7)

6/11 www.uhu.com



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 6)

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	LD/LC50 values relevant for classification:		
Hydrocarl	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics		
Oral	LD50	>5840 mg/kg (rat)	
Dermal	LD50	>2920 mg/kg (rat)	
Inhalative	LC50/4 h	>23.3 mg/l (rat)	
110-82-7	110-82-7 cyclohexane		
Oral	LD50	>5000 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	32.88 mg/l (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity

Not applicable.

Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · Acute effects (acute toxicity, irritation and corrosivity) Not applicable.
- · Sensitisation Not applicable.
- Repeated dose toxicity Not applicable.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

(Contd. on page 8)

www.uhu.com 7/11



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 7)

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information	
· 14.1 UN number or ID number · ADR/ADN, IMDG, IATA	UN1133
14.2 UN proper shipping name	
· ADR/ADN	1133 ADHESIVES
· IMDG	ADHESIVES, MARINE POLLUTANT
· IATA	ADHESIVES

(Contd. on page 9)

www.uhu.com 8/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR/ADN





· Class 3 (F1) Flammable liquids.

Label

·IMDG





· Class 3 Flammable liquids.

· Label

·IATA



· Class 3 Flammable liquids.

· Label

· 14.4 Packing group

· ADR/ADN, IMDG, IATA

• 14.5 Environmental hazards: Product contains environmentally hazardous

substances:

• Marine pollutant: Symbol (fish and tree)• Special marking (ADR/ADN): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): -

· EMS Number: F-E,S-D

· Stowage Category A

14.7 Maritime transport in bulk according to

IMO instruments Not applicable.

· Transport/Additional information:

Quantity limitationsOn passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L

· ADR/ADN

Limited quantities (LQ)Excepted quantities (EQ)Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000

ml

(Contd. on page 10)

· IE

www.uhu.com 9/11



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.03.2025 Version number 16 (replaces version 15) Revision: 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

	(Contd. of page	
Transport category Tunnel restriction code	3 E	
IMDG Limited quantities (LQ)	5L	
Excepted quantities (ÉQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml	
Remarks:	For substances with class 3 according to IMDO Code chapter 2.3.2.2 packing group is classified in packing group. III, as viscosity is in accordance with requirements (flow time t > 100s).	
UN "Model Regulation":	UN 1133 ADHESIVES, 3, III ENVIRONMENTALLY HAZARDOUS	

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 57
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)

www.uhu.com 10/11



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Revision: 22.03.2025 Version number 16 (replaces version 15) Printing date 22.03.2025

Trade name: UHU POR FB 50ML*10 L345

(Contd. of page 10)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	Bridging principles	
Skin corrosion/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long- term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

· Department issuing SDS: PSRA

· Contact: PSRA

· Date of previous version: 27.10.2022 · Version number of previous version: 15

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning

the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

11/11 www.uhu.com